

# uniK



Ha Kyung (Baby Vox, LPG, ...) after installing a pair of uniK 08 at JangChung Studio A on the console



Jürgen Roth (Der rote Baron, Der Schuh des Manitu, ...) presents his new uniK 04



Artist Das Bo is checking out the uniK series next to nEar08 eXperience



The production studio of Radio 7 with Oliver Deckenhoff & uniK 05



Jean-Claude Ades (DJ, Producer, i.e. I Begin to Wonder for Pannii Minoguel) after adding uniK 05 to his workstation



Tai Jason (Towercraft, Sido, Samy Deluxe, ...) with a complete set of ESU studio monitors in his studio in Munich, Germany



TJ Gyger (H2U Online, musical director DJ Bobo) with uniK 05



Thies Steiner (drums DJ Bobo) at H2U Studio in Thun, Switzerland, equipped with uniK 05 and uniK 08



JangChung Studio B in Seoul, Korea (Old Boy, 2 Track, ...) using uniK 05 for editing movie soundtracks and recording vocals



Sound Designer Diego Stocco (Spectrasonics, Sherlock Holmes, Crank, Assassin's Creed Revelations, ...) with his pair of uniK 08



Timo Klinge from Ambient Recording editing his underwater hydrophone surround content using uniK 05



Designed in  
Germany



## uniK 04

## uniK 05

## uniK 08

Type  
Dimensions & Weight  
High Frequency Driver  
Low Frequency Driver  
Output Power  
Frequency Response  
Crossover Point  
Input Impedance  
SPL  
Rated Noise Power  
Input Sensitivity  
Input Connectors

2-Way Speaker System (1 amplified / 1 passive)  
150mm x 210mm x 160mm; 2.45kg / 2.10kg  
1" Silk Dome Tweeter  
4" Kevlar Curved Cone (Magnetic Shielding Type)  
50W (HF & LF); 50W AC consumption  
55Hz - 20kHz  
5.7kHz  
27kOhm balanced / unbalanced  
82dB ±3dB @1W / 1M at 300. 400. 500. 600 Hz  
15W (THD1%, 4ohm load, 1kHz)  
135mV@1W; 525mV@15W (1kHz)  
2 TRS 1/4" (6.3mm) balanced / unbalanced

2-Way Powered Speaker System  
190mm x 265mm x 210mm; 4.28kg  
Ribbon Tweeter  $\Phi$  49mm x 26mm  
5" Kevlar Curved Cone (Magnetic Shielding Type)  
60W (HF: 30W, LF 30W); 85W AC consumption  
49Hz - 22kHz  
2.5kHz  
42kOhm balanced / 8.5kOhm unbalanced  
89dB ±3dB @1W / 1M at 300. 400. 500. 600 Hz  
25W (THD=1%, 4ohm load, 1kHz)  
60mV@1W; 300mV@25W (500 Hz)  
XLR / TS 1/4" (6.3mm) combo balanced / unbalanced

Bi-Amp 2-Way Powered Speaker System  
252mm x 352mm x 319mm; 7.90kg  
Ribbon Tweeter  $\Phi$  49mm x 26mm  
8" Kevlar Curved Cone (Magnetic Shielding Type)  
90W (HF: 30W, LF 60W); 130W AC consumption  
37Hz - 20kHz  
2.4kHz  
42kOhm balanced / 8.5kOhm unbalanced  
90dB ±3dB @1W / 1M at 300. 400. 500. 600 Hz  
45W (THD=1%, 4ohm load, 1kHz)  
75mV@1W; 485mV@45W (1 kHz)  
XLR / TS 1/4" (6.3mm) combo balanced / unbalanced